

A 100% clear acrylic, low VOC sealer that will enhance and protect previously coated and bare cement roof tiles. This single component, solvent-free sealer will help protect roof tiles, improve dirt resistance, and the cured surface is mildew & algae resistant. This product can be used on flat cement tiles, barrel cement tiles, asphalt shingles and previously painted surfaces.

APPLICATION

May be applied by:

Brush (use nylon/polyester),

Roller (use 3/8" nap cover),

Spray (Airless Pressure 2000 psi

Tip .017")

For most applications to previously coated surfaces, one coat of DUX Roof Tile Sealer will be sufficient. Two coats are required for maximum performance and uniform appearance on bare concrete surfaces. This product will apply milky white and dry clear in approximately 1 hour. DO NOT THIN.

DRY TIME (at 77°F & 50% relative humidity)

To touch: 2 hours

To recoat: 4 hours

CAUTIONS

Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory (NIOSH approved) protection or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container close when not in use. Do not transfer contents to other containers for storage.

FIRST AID

In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DUX PAINT

CLEAR

ROOF TILE SEALER

Water Repellant

Low VOC

Restores & Protects

Semi-Gloss Finish

PROTECT FROM FREEZING

CONTENTS: FIVE US GALLONS

SURFACE PREPARATION

WARNING: Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead and other hazardous substances requires the use of proper protective equipment, such as properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Uncoated: Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, peeling and defective coatings, chalk, form release agents, moisture curing materials, etc. Remove all mildew. Allow the surface to dry thoroughly. Sand glossy surfaces dull. Concrete and mortar must be cured – usually about 30 days.

Previously Painted: All old, peeling, flaking paint must be removed.

CLEANUP INFORMATION Clean hands, tools and spills and spatters immediately with soap and warm water. After cleaning, flush spray equipment to prevent rusting of the equipment.

INGREDIENTS CAS#

Water	7732-198-05
Acrylic Polymer	Proprietary
Ester Alcohol	25265-77-4

VOC: 0.82 lbs/gal

KEEP OUT OF REACH OF CHILDREN

Manufactured by:

DUX PAINTS

18 MILL STREET LODI, NJ 07644