

Acrylic Water Borne Polyurethane, Product #WB-544

Description: Extremely durable acrylic polyurethane. It is a non yellowing, fast drying ultra clear coating formulated to protect preserve and enhance the richness of wood floors, cabinets, chairs, tables doors and furniture. For use on floors, doors, wood trim, furniture, cabinets, and paneling.

Color(s): Clear

Finish: High Gloss, Semi-Gloss, Satin

Vehicle type: Acrylic Urethane

Solvent type: Water

VOC: 1.39 Lbs/Gallon (167 Grams/Liter)

Flash point: N/A

Solids by volume: 29%

Weight per gallon: 10.5

Coverage: Theoretical coverage at 1 mil dry is 460 square feet per gallon, and 230 square feet at 2 mils dry.

Viscosity: 50-60 seconds #2 Zahn

Surface preparation: Raw wood: All surfaces should be clean and dry prior to sanding. Avoid using fillers with contain steirates or wax. Painted Wood: Sand old finish if in poor condition. If wax, shellac or steirates are present remove it completely.

Shelf life: 12 Months

Mixing: Stir thoroughly and apply as it comes from the container.

Recommended dry film: 2 Mils

Recommended dry time: Dries in 1 hour, can be recoated in 2 hours

Recommended primers: Water Reducible Sealer

Safety information: Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648