

## Acrylic Water Borne Enamel, Product #850

**Description:** Extremely durable acrylic enamel, which has excellent adhesion and abrasion resistance. For use on interior – exterior surfaces where maximum durability is desired. Excellent for use over primed or previously painted metal, including galvanized steel, previously painted wood, plaster, wallboard, concrete, brick, cinder and concrete block.

**Color(s):** All colors

**Finish:** High Gloss, Semi-Gloss

**Vehicle type:** Acrylic

**Solvent type:** Water

**VOC:** 228Grams/Liter

**Flash point:** N/A

**Solids by volume:** 33.75% white, Varies by color

**Weight per gallon:** 10.25 Lbs

**Coverage:** Theoretical coverage at 1 mil dry is 540 square feet per gallon.

**Viscosity:** 85-95 KU

**Surface preparation:** Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Bare wood and other rough surfaces should be sanded smooth. Glossy areas should be dulled by sanding. Painted surfaces: Hand or power toll clean (SSPC-SP-2 or SSPC-SP-3), and spot prime.

**Shelf life:** 12 Months

**Mixing:** Stir thoroughly and apply as it comes from the container.

**Recommended dry film:** 2 Mills

**Recommended dry time:** Dries in 1 hour, can be recoated in 4 hours

**Recommended primers:** Universal primer, Water reducible primer, Water based Epoxy Primer

**Safety information:** Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

**Dux Paint LLC.**

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648