

## Dry Fog – Dry Fall, Product #002

**Description:** Dux Alkyd dry fog is an economical alkyd dry fog coating suitable for interior spray applications on all surfaces. Ideal for finishing large industrial or commercial ceilings and wall surfaces. When spraying it produces a minimal amount of overspray, which can be brushed away with a broom or brush. Substrates: Concrete Stucco, Dry Wall, Ferrous Metals, Masonry, Plaster, Wood

**Color(s):** All colors available

**Finish:** Flat

**Vehicle type:** Modified Resin

**Solvent type:** N/A

**VOC:** N/A

**Flash point:** 105° F. Seta Flash

**Solids by volume:** 60% +/- 2%

**Weight per gallon:** 13.29 Lbs

**Coverage:** Theoretical coverage at 8 Mills Wet is 200 square feet per gallon, Theoretical coverage @ 1 mil is 690 square feet per gallon.

**Viscosity:** 85-90 KU (Kreb Units)

**Surface preparation:** Remove all grease, dirt, oil, wax and other foreign matter from surfaces by washing with a warm solution of household detergent, rinsing with clean water and allowing to dry thoroughly.

**Shelf life:** 12 Months

**Mixing:** Stir thoroughly and apply as it comes from the container.

**Recommended dry film:** 2-3 Mills

**Recommended dry time:** Dries in 10 minutes @77° F. Can be recoated in 4 hours.

**Recommended primers:** N/A

**Safety information:** Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

**Dux Paint LLC.**

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648