

Interior Alkyd Enamel, Product #400-429

Description: An exceptional lead & chromate free low VOC interior/exterior alkyd paint for use on interior/exterior surfaces. For new or previously painted surfaces. Used on wood, metal concrete. For doors, trim, dados, railings, machinery, metal partitions, and factory equipment.

Color(s): All colors available

Finish: High Gloss

Vehicle type: Alkyd

Solvent type: N/A

VOC: 2.82 Lbs/Gallon, 340 Grams/Liter

Flash point: 105° F. Set Flash

Solids by volume: 57.28%

Weight per gallon: 9.77 Lbs

Coverage: Theoretical coverage at 1 mil dry is 916 square feet per gallon, and 458 square feet at 2 mils dry.

Viscosity: 80-90 KU (Kreb Units)

Surface preparation: Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Bare wood and other rough surfaces should be sanded smooth. Glossy areas should be dulled by sanding.

Shelf life: 12 Months

Mixing: Stir thoroughly and apply as it comes from the container.

Recommended dry film: 2 Mil

Recommended dry time: Dries to touch in 4 Hours. Can be recoated in 8-12 hours.

Recommended primers: N/A

Safety information: Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648