

## Chlorinated Rubber Pool Paint, Product #650

**Description:** A Chlorinated rubber based pool paint and sealer new or old concrete pools. Excellent for fresh or salt water. Resists fading, fungus, algae.

**Color(s):** White, Black, Royal Blue, Ocean Blue, Aquamarine, Red

**Finish:** Semi-Gloss

**Vehicle type:** Chlorinated Rubber

**Solvent type:** Aliphatic & Aromatic hydrocarbons

**VOC:** N/A

**Flash point:** 54° F

**Solids by volume:** 33.3%

**Weight per gallon:** 11.5 Lbs mixed

**Coverage:** Theoretical coverage at 1 mil dry is 532 square feet per gallon, and 266 square feet at 2 mils dry.

**Viscosity:** 70-80 KU (Kreb Units)

**Surface preparation:** Remove all grease, dirt, oil, wax and other foreign matter from surfaces. New concrete pools must be etched with 10% muriatic acid, easily applied until it ceases to effervesce. Then thoroughly rinse with clean water and allow to dry. On previously painted surfaces clean with pool cleaner to eliminate the scum, oil, dirt, then flush with clean water, and let dry. **WAIT 7 DAYS BEFORE FILLING POOL WITH WATER.**

**Shelf life:** 12 Months

**Mixing:** Stir thoroughly and apply as it comes from the container

**Recommended dry film:** N/A

**Recommended dry time:** Set to touch in 30 Minutes. Recoat in 12 hours. Wait 7 days after final coat to fill pool.

**Recommended primers:** Self Priming

**Safety information:** FLAMMABLE! HARMFUL OR FATAL IF SWALLOWED, FLAMMABLE LIQUID AND VAPOR, SKIN AND EYE IRRITANT. CONTAINS MINERAL SPIRITS, XYLENE, TOLUENE AND HIGH FLASH NAPHTHA. Vapor harmful, may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648