

Epoxy Pool Paint, Product #522

Description: A two component, 1:1 ratio polyamide cured epoxy Coating formulated for use on all pools, Weathered Concrete, Steel, Fiberglass or aluminum. For use in fresh or salt water pools.

Color(s): White, Black, Royal Blue, Ocean Blue, Aquamarine, Red

Finish: Gloss

Vehicle type: Epoxy Resins & polyamide curing agents

Solvent type: Glycol Ether, Aromatic hydrocarbons, Xylene

VOC: N/A

Flash point: 81° F. (mixed)

Solids by volume: 50%

Weight per gallon: 9.5 Lbs (mixed)

Coverage: Theoretical coverage at 1 mil dry is 800 square feet per gallon, and 400square feet at 2 mils dry.

Viscosity: 75-85 KU

Surface preparation: Remove all grease, dirt, oil, wax and other foreign matter from surfaces. New concrete pools must be etched with 10% muriatic acid, easily applied until it ceases to effervesce.

Shelf life: 12 Months

Mixing: Mix Ratio: 1:1 By Volume. Stir thoroughly each component, combine in proper ratio. Give ½ hour induction period before using. Mix only what will be used in an 8 hour period.

Recommended dry film: 2 Mils

Recommended dry time: Set to touch in 1-2 Hours. Recoat within 18 hours. Fully cured in 7 Days.

Recommended primers: N/A

Safety information: FLAMMABLE! HARMFULL OR FATAL IF SWALLOWED, FLAMMABLE LIQUID AND VAPOR, SKIN AND EYE IRRITANT. CONTAINS GLYCOL ETHER, HIGH FLASH NAPHTHA AND XYLENE. Vapor harmful, may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648