

# EXTERIOR WATERBASE FINISH

#750

---

<b>PRODUCT NAME:</b>	Exterior Waterbased Finish / House Paint
<b>PRODUCT NUMBERS:</b>	#750
<b>DESCRIPTION:</b>	A new generation Exterior acrylic emulsion paint that is flexible and outperforms ordinary paint.
<b>SUGGESTED USES:</b>	Wood, Masonry, Siding, Asbestos Shingles, Stucco, Brick, Pressboard Siding and primed metal.
<b>COLORS:</b>	White, Navajo White, Tudor Brown, Cottage Red, Platinum Gray, Richmond Bisque (Custom Colors Available)
<b>FINISH:</b>	Eggshell (low sheen)
<b>VEHICLE TYPE:</b>	Vinyl Acrylic
<b>SOLVENT TYPE:</b>	Water
<b>VOC:</b>	.096 Lbs/Gallon (115 Grams/Liter)
<b>FLASH POINT:</b>	Not Applicable
<b>SOLIDS BY VOLUME:</b>	43.4%
<b>WEIGHT PER GALLON:</b>	10.7 Lbs
<b>RECOMMENDED DRY FILM:</b>	3 Mils
<b>COVERAGE:</b>	Theoretical coverage at 1 mil dry is 690 square feet per gallon, and 230 square feet at 3 mils dry.
<b>VISCOSITY:</b>	110-120 KU (Kreb Units)
<b>RECOMMENDED DRY TIME:</b>	Set to Touch in 1 hour. Recoat in 4 Hours.
<b>REDUCER:</b>	Not Recommended
<b>CLEAN UP:</b>	Water
<b>PHYSICAL PROPERTIES:</b>	Extremely durable and flexible as well as mildew resistant. Its superior sealing properties seals cracks, bridges gaps and acts as a sealant to prevent moisture penetration.
<b>RECOMMENDED PRIMERS:</b>	Self Priming On most Substrates.
<b>SURFACE PREPERATION:</b>	Remove all grease, dirt, oil, wax and other foreign matter from surfaces. Surface should be clean and contaminant free.

**APPLICATION:**

Brush, Roller Spray.

Roll: ¼ - ½ synthetic roller cover. Or ½” Lambswool. Keep Roller Wet. Roll in one direction. Do not over roll.

**Conventional Air Spray:**

Spray Gun:

**Binks**

#18

Or #62

**Graco**

800

**Devilbiss**

JGA502

or MBC-510

Fluid Nozzle:

66 or 63C

.070

FF or E

Air Cap:

66PE or 63PB

106-805

704,765,78

**Airless Spray:**

Pump:

**Binks**

37:1 B8-36

**Graco**

30:1 Bulldog

Pressure Filter:

60 Mesh

Fluid Hose:

71-7507 x 100

¼ “ x 50’

Airless Gun

1M

Contractor

Tips:

9-1860-9-2180

.015-.019

Minimum Pressure:

2000-2500 PSI

**HVLP:**

Spray Gun:

**Binks**

Mach 1

**Graco**

Optimizer

Fluid Nozzle:

94F or 97F

276-296

Orifice

.055 or .070

.086

Air Nozzle:

95AP or 97AP

188-756

**POT LIFE:**

Not Applicable

**SHELF LIFE:**

12 Months minimum.

**MIXING:**

Stir thoroughly and apply as it comes from the container.

**SAFETY INFORMATION:**

Do not take internally. Close container after each use. Keep from freezing. **KEEP OUT OF REACH OF CHILDREN.**