

# LATEX SEMI GLOSS

#430

---

<b>PRODUCT NAME:</b>	Latex Semi Gloss
<b>PRODUCT NUMBERS:</b>	430 to 439
<b>DESCRIPTION:</b>	A water based Vinyl latex, which provides an ideal coating for interior surfaces.
<b>SUGGESTED USES:</b>	For interior use on wallboard, plaster, masonry, on walls and trim. For previously painted surfaces or primed wood or metal.
<b>COLORS:</b>	Available in all Colors
<b>FINISH:</b>	Semi Gloss
<b>VEHICLE TYPE:</b>	Vinyl latex
<b>SOLVENT TYPE:</b>	Water
<b>VOC:</b>	1.70 Lbs/Gallon (2.04 Grams/Liter)
<b>FLASH POINT:</b>	Not Applicable
<b>SOLIDS BY VOLUME:</b>	27.43%
<b>WEIGHT PER GALLON:</b>	9.72 Lbs
<b>RECOMMENDED DRY FILM:</b>	2 Mils
<b>COVERAGE:</b>	Theoretical coverage at 1 mil dry is 438 square feet per gallon, and 220 square feet at 2 mils dry.
<b>VISCOSITY:</b>	80-95 KU
<b>RECOMMENDED DRY TIME:</b>	Sets to touch in 1-2 hours. Can be recoated in 8 hours.
<b>REDUCER:</b>	Water
<b>CLEAN UP:</b>	Soap & Water
<b>RECOMMENDED PRIMERS:</b>	For New Wallboard: PVA Primer, For Wood: Alkyd Primer, For Metal: Metal Primer
<b>SURFACE PREPERATION:</b>	Remove all grease, dirt, oil, wax and other foreign matter from surfaces.

**DUX PAINT LLC.**

OFFICE ADDRESS: 18 Mill Street, Lodi NJ 07644  
(973) 473-2376 - FAX. (973) 473-1648

**POT LIFE:** Not Applicable

**SHELF LIFE:** 12 Months minimum.

**APPLICATION:** Brush, Roller Spray.  
Roll: ¼ " lambswool or ¼" – ½" synthetic roller cover

	<b>Conventional Air Spray:</b>	<b>Binks</b>	<b>Graco</b>	
<b>Devilbiss</b>				
JGA502	Spray Gun:	#18	800	
MBC-510		Or #62	or 900	or
or E	Fluid Nozzle:	66 or 67	047 or 086	D
704,765,78	Air Cap:	66PE or 63PB	02,03, 952	
	<b>Airless Spray:</b>	<b>Binks</b>	<b>Graco</b>	
	Pump:	37:1 B8-36	30:1 Bulldog	
	Pressure Filter:		60 Mesh	
	Fluid Hose:	71-7507x 100'		
	Airless Gun	M1	208-663	
	Tips:	9-1860-9-2180	.015-.019	
	Minimum Pressure:		2000 PSI	
	<b>HVLP:</b>	<b>Binks</b>		
	Spray Gun:	Mach 1		
	Fluid Nozzle:	94F or 905F		
	Orifice	.007 or .086		
	Air Nozzle:	95P or 905P		

**MIXING:** Stir thoroughly and apply as it comes from the container.  
For Spraying thin water for spray viscosity.

**SAFETY INFORMATION:** Do not take internally. Close container after each use.  
Keep from freezing. **KEEP OUT OF REACH OF CHILDREN.**

All technical data, recommendations and services are accurate to the best of our knowledge. Seller assumes no responsibility for the results obtained or damages incurred from their use by the Buyer in whole or in part. No Warranty, including those of merchantability or fitness for a particular purpose, is expressed or implied since the method of application and its use is beyond our control. There are no warranties, which extend beyond the description or the face hereof.