

LATEX TRAFFIC PAINT

#336

PRODUCT NAME:	Latex Traffic Paint
PRODUCT NUMBERS:	#336
DESCRIPTION:	A new generation 100% acrylic emulsion traffic paint. It's a fast drying interior – exterior, VOC Compliant line marking paint.
SUGGESTED USES:	For use on concrete, asphalt, curbs, parking lots, warehouse aisles, and storage areas.
COLORS:	White, Yellow, Lead free Yellow, Blue
FINISH:	Flat
VEHICLE TYPE:	Acrylic
SOLVENT TYPE:	Water
VOC:	.8 Lbs/Gallon (96 Grams/Liter)
FLASH POINT:	Not Applicable
SOLIDS BY VOLUME:	59%
WEIGHT PER GALLON:	14 Lbs (White)
RECOMMENDED DRY FILM:	7-9 Mils (recommended wet film- 14-16)
COVERAGE:	Lineal coverage at 14-16 mil Wet is 3" line 420-470 lineal Feet per gallon, 4" line 315-355 lineal Feet per gallon,
VISCOSITY:	85-100 KU (Kreb Units)
RECOMMENDED DRY TIME:	Dries in 30 Minutes. No Traffic Pickup.
REDUCER:	Water
CLEAN UP:	Soap & Water
PHYSICAL PROPERTIES:	ASTM D522 Flexibility (conical Mandrel) – Pass
SURFACE PREPERATION:	Remove all grease, dirt, oil, excess water and other foreign matter from surface. Surface should be dry and free of loose paint.
POT LIFE:	Not Applicable
SHELF LIFE:	12 Months minimum.

DUX PAINT LLC.
OFFICE ADDRESS: 18 Mill Street, Lodi NJ 07644
(973) 473-2376 - FAX. # (973) 473-1648

RECOMMENDED PRIMERS:

Not Applicable

APPLICATION:

Brush, Roller or Conventional or Airless Spray.

Roll: ¾" synthetic roller cover

Spray: Line marking Spray equipment.

Binks Line Marking Equipment:

Spray Gun: 21M –61M –95AM

Nozzle Setup: 6755 X 709 Internal mix Low Speed

Nozzle Setup: 6895 X 713 Internal Fast Speed

MIXING:

Stir thoroughly and apply as it comes from the container.

SAFETY INFORMATION:

Do not take internally. Close container after each use. Keep from freezing. **KEEP OUT OF REACH OF CHILDREN.**