

SOLVENT BASED TRAFFIC PAINT

TTP85-TP

PRODUCT NAME:	Solvent Based Traffic Paint	
PRODUCT NUMBERS:	TTP85-TP	
DESCRIPTION:	A quick dry, VOC compliant, interior & exterior traffic marking paint. Resistant to abrasion, oils, grease and severe weather.	
SUGGESTED USES:	For use on traffic lines, crosswalks, curbs, parking lots, storage areas. Can be broadcast with glass beads for increased night vision.	
COLORS:	White, Yellow, Lead Free Yellow	
FINISH:	Flat	
VEHICLE TYPE:	Alkyd	
SOLVENT TYPE:	Aromatic Hydrocarbons	
VOC:	2.0 Lbs/Gallon (270Grams/Liter)	
FLASH POINT:	45° F. Seta Flash	
SOLIDS BY VOLUME:	14.88 Lbs/Gallon	
WEIGHT PER GALLON:	14.88 Lbs/Gallon	
RECOMMENDED DRY FILM:	7-9 Mil (recommended wet film- 10-12)	
COVERAGE:	Lineal coverage at 10-12 mil Wet is 3" line 375-450 lineal Feet per gallon, 4" line 280-335 lineal Feet per gallon,	
VISCOSITY:	90-100 KU (Kreb Units)	
RECOMMENDED DRY TIME:	Dries in 30 Minutes – No pickup	
REDUCER:	Ready for use, no reducer needed	
CLEAN UP:	Toluene	
PHYSICAL PROPERTIES:	ASTM D968	Abrasion Resistance (Falling Sand) 50 Liters - Pass
	ASTM D522	Flexibility (conical mandrel) ¼" - Pass
SURFACE PREPERATION:	Remove all grease, dirt, oil, excess water and other foreign matter from surface. Surface should be dry and free of loose paint. Do not apply over moisture or if temperature is below 40° F. Try test pattern on asphalt for bleeding. If bleeding occurs use Latex Traffic Paint.	

DUX PAINT LLC.

OFFICE ADDRESS: 18 mill STREET, LODI NJ 07644
(973)473-2376 FAX# (973)473-1648

APPLICATION:	Brush, Roller or Conventional or Airless Spray. Roll: ¾" synthetic roller cover Spray: Line marking Spray equipment. Binks Line Marking Equipment: Spray Gun: 21M –61M –95AM Nozzle Setup: 6755 X 709 Internal mix Low Speed Nozzle Setup: 6895 X 713 Internal Fast Speed
POT LIFE:	Not Applicable
SHELF LIFE:	12 Months minimum.
MIXING:	Stir thoroughly and apply as it comes from the container.
SAFETY INFORMATION:	FLAMMABLE! HARMFUL OR FATAL IF SWALLOWED, FLAMMABLE LIQUID AND VAPOR, SKIN AND EYE IRRITANT. TOLUENE. Keep away from heat, sparks and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave area. Do not take internally. Close container after each use. Avoid contact with skin or eyes.
FISRT AID:	If swallowed, do not induce vomiting. Call a physician immediately. In case of eye contact, immediately flush thoroughly with water and call a physician. For skin contact, wash thoroughly. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. REGULAR YELLOW TRAFFIC PAINT CONTAINS LEAD. DRIED FILM OF THIS PAINT MAY BE HARMFUL IF EATEN OR CHEWED. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

All technical data, recommendations and services are accurate to the best of our knowledge. Seller assumes no responsibility for the results obtained or damages incurred from their use by the Buyer in whole or in part. No Warranty, including those of merchantability or fitness for a particular purpose, is expressed or implied since the method of application and its use is beyond our control. There are no warranties that extend beyond the description or the face hereof.