

# WATER BASED POOL PAINT

WB-650

---

<b>PRODUCT NAME:</b>	Water Based Pool Paint
<b>PRODUCT NUMBERS:</b>	.....WB-650
<b>DESCRIPTION:</b>	A new generation water based acrylic pool paint that has excellent adhesion to most types of pool coatings that are in good condition. For use on bare concrete and plaster. It is low VOC and is environmentally friendly. Quick drying for easy re-coat.
<b>SUGGESTED USES:</b>	Interior or exterior use on fresh or salt water pools.
<b>COLORS:</b>	Red, white, black, royal blue, ocean blue, aquamarine
<b>FINISH:</b>	Semi Gloss
<b>VEHICLE TYPE:</b>	Acrylic
<b>SOLVENT TYPE:</b>	Glycol ether, Water
<b>FLASH POINT:</b>	Not applicable
<b>SOLIDS BY VOLUME:</b>	42% (white)
<b>RECOMMENDED DRY FILM:</b>	2 Mils
<b>COVERAGE:</b>	Theoretical coverage at 1 mil dry is 674 square feet per gallon, and 337 square feet at 2 mils dry.
<b>VISCOSITY:</b>	75-90 KU (Kreb Units)
<b>RECOMMENDED DRY TIME:</b>	Sets to touch in 15 minutes.. Can be recoated in 4 hours. Allow a minimum of 3 days for complete cure.
<b>REDUCER:</b>	Water
<b>CLEAN UP:</b>	Soap & Water
<b>RECOMMENDED PRIMERS:</b>	Self Priming
<b>APPLICATION:</b>	Brush, Roller Spray.
<b>SURFACE PREPERATION:</b>	Remove all grease, dirt, oil, wax and other foreign matter from surfaces. New concrete pools must be etched with 10% muriatic acid, easily applied until it ceases to effervesce. Then thoroughly rinse with clean water and allow to dry. On previously painted surfaces clean with pool cleaner to eliminated the scum, oil, dirt, then flush with clean water, and let dry. Glossy surfaces and pools with epoxy coatings should be sanded before applying.

**DUX PAINT LLC.**

OFFICE ADDRESS: 18 mill STREET, LODI NJ 07644  
(973)473-2376 FAX# (973)473-1648

<b>Conventional Air Spray:</b>	<b>Binks</b>	<b>Graco</b>	<b>Devilbiss</b>
Spray Gun:	#18 Or #62	800	JGA502 or MBC-510
Fluid Nozzle:	66 or 63C	03 or 04	FF or E
Air Cap:	66PE or 63PW	02, 03, 021	704,765,78
<b>Airless Spray:</b>	<b>Binks</b>	<b>Graco</b>	
Pump:	98-999	30:1 Bulldog	
Pressure Filter:		60 Mesh	
Fluid Hose:	71-7705x 50'	1/4" x 50' or 3/8" x 100'	
Airless Gun	M1	208-663	
Tips:	9-1860-9-1540	.015-.019	
Minimum Pressure:		2000 PSI	
<b>HVLP:</b>	<b>Binks</b>		
Spray Gun:	Mach 1		
Fluid Nozzle:	94F or 97F		
Orifice	.055 or .070		
Air Nozzle:	95AP or 97AP		

**POT LIFE:** Not Applicable

**SHELF LIFE:** 12 Months minimum.

**MIXING:** Stir thoroughly and apply as it comes from the container.

**SAFETY INFORMATION:** Do not take internally. Close container after each use. Avoid contact with skin or eyes. **HARMFUL IF SWALLOWED, VAPOR HARMFUL, CONTAINS ETHYLENE GLYCOL PROPYL ETHER.** May effect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose throat and skin irritation. **First Aid:** In case of eye contact hold eye lids open and immediately flush with plenty of water for at least 15 minutes. Get medical attention. In case of skin contact wash thoroughly with soap and water. If irritation persists seek medical attention. If affected by by breathing vapor, remove to fresh air. If continued difficulty persists get medical attention. If swallowed do not induce vomiting, call a physician. Use only with adequate ventilation. Do not breath vapor, mist or fumes. Avoid contact with eyes and skin. Do not take internally. Wash exposed areas after contact and before eating, drinking, using tobacco or bathroom.

**KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION**

All technical data, recommendations and services are accurate to the best of our knowledge. Seller assumes no responsibility for the results obtained or damages incurred from their use by the Buyer in whole or in part. No Warranty, including those of merchantability or fitness for a particular purpose, is expressed or implied since the method of application and its use is beyond our control. There are no warranties that extend beyond the description or the face hereof.