

## Acrylic Latex Primer, Product #398

**Description:** A water-based Vinyl /acrylic latex Primer which provides an ideal Primer coat to be top coated with most finish coats. For interior use on wallboard, plaster, masonry, on walls and ceilings.

**Color(s):** White

**Finish:** Flat

**Vehicle type:** Acrylic, Vinyl Latex

**Solvent type:** Water

**VOC:** 0.74Lbs/Gallon, 88Grams/Liter

**Flash point:** N/A

**Solids by volume:** 35%

**Weight per gallon:** 11.51Lbs

**Coverage:** Theoretical coverage at 1 mil dry is 560 square feet per gallon, and 280 square feet at 2 mils dry

**Viscosity:** 80-95 KU

**Surface preparation:** Remove all grease, dirt, oil, wax and other foreign matter from surfaces.

**Shelf life:** 12 Months

**Mixing:** Stir thoroughly and apply as it comes from the container. For Spraying thin water for spray viscosity.

**Recommended dry film:** 2 Mil

**Recommended dry time:** Sets to touch in 30 minutes. Can be top coated in 4 hours.

**Recommended primers:** N/A

**Safety information:** Do not take internally. Close container after each use. Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

**Dux Paint LLC.**

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648