

Brick & Concrete sealer, Product #ACS-10

Description: A new generation water based acrylic brick, concrete sand masonry that has excellent adhesion to most types of cementitious substrates that are in good condition. For use on bare concrete brick and plaster. It is low VOC and is environmentally friendly. Quick drying for easy re-coat.

Color(s): Clear, colors available

Finish: Semi-Gloss

Vehicle type: Acrylic

Solvent type: Glycol ether, Water

VOC: N/A

Flash point: N/A

Solids by volume: 31% clear

Weight per gallon: N/A

Coverage: Theoretical coverage at 1 mil dry is 500 square feet per gallon, and 250 square feet at 2 mils dry.

Viscosity: 70-80 KU (Kreb Units)

Surface preparation: Remove all grease, dirt, oil, wax and other foreign matter from surfaces. New concrete pools must be etched with 10% muriatic acid, easily applied until it ceases to effervesce. Then thoroughly rinse with clean water and allow to dry.

Shelf life: 12 Months

Mixing: Stir thoroughly and apply as it comes from the container

Recommended dry film: 2 mils

Recommended dry time: Sets to touch in 15 minutes.. Can be recoated in 4 hours. Allow a minimum of 3 days for complete cure.

Recommended primers: Self Priming

Safety information: Do not take internally. Close container after each use. Avoid contact with skin or eyes. HARMFUL IF SWALLOWED, VAPOR HARMFUL, CONTAINS ETHYLENE GLYCOL PROPYL ETHER. May effect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose throat and skin irritation. First Aid: In case of eye contact hold eye lids open and immediately flush with plenty of water for at least 15 minutes. Get medical attention. In case of skin contact wash thoroughly with soap and water. If irritation persists seek medical attention. If affected by breathing vapor, remove to fresh air. If continued difficulty persists get medical attention. If swallowed do not induce vomiting, call a physician. Use only with adequate ventilation. Do not breath vapor, mist or fumes. Avoid contact with eyes and skin. Do not take internally. Wash exposed areas after contact and before eating, drinking, using tobacco or bathroom. KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION

Dux Paint LLC.

18 Mill Street, Lodi NJ 07644

Office - (973)-473-2376, Fax - (973)-473-1648